

MODEL	HP	Bending Moment	Pipe Capacity	O.D. Tube Capacity	Round Rod	Approx. Wt.	Spindle	Floor Space
A-1	1	2,800 In-Lbs	3/4"Scd. 40	1.000" x 0.125" Wall	0.750"∅	650 Lbs	2.00"	24" x 24"
A-3	3	9,000 In-Lbs	1-1/4"Scd. 40	1.625" x 0.125" Wall	1.250"∅	1,600 Lbs	3.00"	36" x 36"
A-5	5	20,000 In-Lbs	2"Scd. 40	2.375" x 0.187" Wall	1.500"∅	1,750 Lbs	3.00"	36" x 36"
A-7	5	28,500 In-Lbs	2"Scd. 40	2.375" x 0.218" Wall	1.750"∅	2,000 Lbs	3.00"	42" x 42"
B-10	10	75,000 In-Lbs	2"Scd. 40	2.875" x 0.187" Wall	2.50" ∅	6,500 Lbs	2.50"	48" x 48"
D-10	10	100,000 In-Lbs	3"Scd. 40	3.500" x 0.312" Wall	3.00" ∅	7,000 Lbs	4.50"	48" x 60"
D-15	15	150,000 In-Lbs	4"Scd. 40	4.500" x 0.375" Wall	n/a	7,500 Lbs	4.50"	60" x 60"
D-20	20	180,000 In-Lbs	5"Scd. 40	5.000" x 0.25" Wall	n/a	800 Lbs	4.50"	60" x 60"
DD-7	5	30,000 In-Lbs	Rod Only	Rod Only	1.75" ∅	1,400 Lbs	n/a	36" x 48"
DD-15	7.5	150,000 In-Lbs	Rod Only	Rod Only	2.50" ∅	3,000 Lbs	n/a	42" x 64"
DD-20	15	300,000 In-Lbs	Rod Only	Rod Only	3.00" ∅	10,000 Lbs	n/a	56" x 93"
E-20	20	255,000 In-Lbs	6"Scd. 40	6.625" x 0.280" Wall	n/a	16,800 Lbs	7.00"	84" x 84"

Capacities based upon mild steels with 36,000 psi yields. Pipe is nominal Schedule 40 or 80 pipe in mild steel.